

movicart

ELECTRIC TUG



MOVICART MTE MTE3500

Movicart MTE3500 is a heavy-duty electric tug designed to safely and effortlessly move existing trolleys and wheeled loads up to 3,500 kg (7,700 lb), reducing operator strain in compliance with ISO 11228 manual handling standards.

Movicart MTE3500 offers maximum reliability and flexibility thanks to a wide range of accessory configurations, allowing quick and secure connection to carts of different designs, sizes, heights, and weights, improving plant safety while increasing overall productivity.

Equipped with oversized tractive wheels **Movicart MTE** ensures smooth, precise maneuverability both indoors and outdoors, even on uneven surfaces, tight spaces, and non-linear paths, easily overcoming obstacles while maintaining full control and operational safety. MTE3500 doesn't require any license and can be adaptable with ballasts depending on the weight to be moved.

CONTROL PANEL

studied to put every driving command at the operator's fingertips. Different mounting heights possible to suit any operator needs

VARIOUS CONFIGURATIONS

wide range of accessories configuration available to effectively connect carts of different dimension

PLUG&PLAY LITHIUM BATTERY

the plug&play eco-friendly lithium battery allows one-handed changes in less than 10 seconds

ANTI-CRUSHING SYSTEM

safety precaution that will reverse direction from backward to forward if Movicart hits the operator

OVERSIZED DRIVE WHEELS


Can operate both indoors and outdoors even on irregular surfaces or non-straight paths

2 YEAR WARRANTY

the only product in its category with a 2-year warranty on both the motor and the battery

MTE3500

Movicart MTE3500 tug is designed to effortlessly pull carts, trolleys or wheeled loads up to 3,500 kg (7,700 lb). Thanks to its various configurations, it can move carts of different sizes, heights and weights. MTE3500 can be adaptable with ballasts depending on the weight to be moved.



model	max tow capacity	motor	battery	max speed	unit weight
MTE 3500	3,500 kg - 7,700 lb	24 V DC IP 44 brushless	lithium 24 V	75 m/min	300 kg - 660 lb